



THE POWER OF THREE³

PHARMCO-AAPER

AND COMMERCIAL ALCOHOLS

Product Information (203) 740-3471

Emergency Assistance CHEMTREC 1-800-424-9300

PRODUCT NAME: MINERAL OIL 35

Manufacturer: PHARMCO-AAPER.
58 Vale Road
Brookfield, Connecticut 06804, USA
Phone (203) 740-3471
Fax (203) 740-3481

1101 Isaac Shelby Drive
Shelbyville, KY 40065
Phone (502) 633-0650
Fax (502) 633-0685

Emergency Contact:

CHEMTREC 1-800-424-9300

I. PRODUCT IDENTIFICATION

SYNONYMS: MINERAL OIL 35 MINERAL OIL USP

NFPA HAZARD IDENTIFICATION

DEGREE OF HAZARD RATINGS

0 - LEAST

HEALTH: 0 1 - SLIGHT

FIRE: 1 2 - MODERATE

REACTIVITY: 0 3 - HIGH

4 - EXTREME

II. INGREDIENTS

HAZARDOUS

COMPONENT NAME IN PERCENTAGE COMPONENT

CAS NUMBER BLEND MIN MAX EXPOSURE LIMITS UNITS

WHITE MINERAL OIL

8042-47-5 NO 100 OSHA PEL NO LIMIT

ACGIH TLV NO LIMIT

III. HEALTH EFFECT INFORMATION

EYE CONTACT:

THIS PRODUCT IS MINIMALLY IRRITATING TO THE EYES UPON DIRECT CONTACT.

BASED ON TESTING OF SIMILAR PRODUCTS AND/OR COMPONENTS.

SKIN CONTACT:

THIS PRODUCT IS NOT EXPECTED TO CAUSE ANY SKIN IRRITATION UPON DIRECT SINGLE OR REPEATED AND PROLONGED CONTACT; HOWEVER, SIMILAR CHEMICAL COMPOSITION PRODUCTS APPLIED TO THE SKIN OF LABORATORY ANIMALS RESULTED IN MINIMAL TO SLIGHT DERMAL IRRITATION.

INHALATION:

THIS PRODUCT HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION HAZARD AT AMBIENT CONDITIONS. CAUTION SHOULD BE TAKEN TO PREVENT AEROSOLIZATION OR MISTING OF THIS PRODUCT. THE PERMISSABLE EXPOSURE LIMIT (PEL) AND THRESHOLD LIMIT VALUE (TLV) FOR THIS PRODUCT AS

OIL MIST IS 5 MG/M3. EXPOSURES BELOW 5 MG/M3 APPEAR TO BE WITHOUT SIGNIFICANT HEALTH RISK. THE SHORT-TERM EXPOSURE LIMIT FOR THIS PRODUCT AS AN OIL MIST IS 10 MG/M3. SEE HEALTH DATA SECTION BELOW.

INGESTION:

INGESTION IS RELATIVELY NON-TOXIC UNLESS ASPIRATION OCCURS. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA. SEE HEALTH DATA SECTION BELOW.

HEALTH DATA:

EXPOSURE TO A LARGE SINGLE DOSE, OR REPEATED SMALL DOSES OF MINERAL OIL BY INHALATION, ASPIRATION OR INGESTION LEADING TO ASPIRATION CAN LEAD TO LIPID PNEUMONIA OR LIPID GRANULOMA. THESE ARE LOW-GRADE, CHRONIC, LOCALIZED TISSUE REACTIONS, WHICH ARE NOT FATAL. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CONCLUDED THAT

HIGHLY REFINED MINERAL OILS ARE GROUP 3 SUBSTANCES, "NOT CLASSIFIABLE AS TO THEIR CARCINOGENICITY TO HUMANS," BASED ON INADEQUATE HUMAN AND INADEQUATE ANIMAL EVIDENCE. IARC HAS ALSO CONCLUDED THAT THERE IS NO EVIDENCE FOR THE CARCINOGENICITY TO EXPERIMENTAL ANIMALS OF WHITE OILS WHEN ADMINISTERED BY ROUTES OTHER THAN BY INTRAPERITONEAL INJECTION. THIS SUBSTANCE IS NOT CARCINOGENIC ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD.

IV. EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER AND CONTINUE FLUSHING UNTIL IRRITATION SUBSIDES. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS AND TAKE VICTIM TO HOSPITAL IMMEDIATELY.

SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING. IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. IF VICTIM IS SEVERELY BURNED, REMOVE TO A HOSPITAL IMMEDIATELY.

INHALATION:

THIS MATERIAL HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION EXPOSURE AT AMBIENT CONDITIONS.

INGESTION:

MAY ACT AS A LAXATIVE. DO NOT INDUCE VOMITING.

V. PERSONAL HEALTH PROTECTION INFORMATION

EYE PROTECTION:

EYE PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF MATERIAL IS HANDLED SUCH THAT IT COULD BE SPLASHED INTO EYES, WEAR PLASTIC FACE SHIELD OR SPLASH-PROOF SAFETY GOGGLES.

SKIN PROTECTION:

NO SKIN PROTECTION IS REQUIRED FOR SINGLE, SHORT DURATION EXPOSURES. FOR PROLONGED OR REPEATED EXPOSURES, USE IMPERVIOUS CLOTHING (BOOTS, GLOVES, APRONS, ETC.) OVER PARTS OF THE BODY SUBJECT TO EXPOSURE. IF HANDLING HOT MATERIAL, USE INSULATED PROTECTIVE CLOTHING (BOOTS, GLOVES, APRONS, ETC.).

RESPIRATORY PROTECTION:

RESPIRATORY PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, USE AN ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER. ALL RESPIRATORS MUST BE NIOSH CERTIFIED. DO NOT USE COMPRESSED OXYGEN IN HYDROCARBON ATMOSPHERES.

VENTILATION:

IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, ADEQUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE MUST BE PROVIDED TO MAINTAIN CONCENTRATIONS BELOW THE SPECIFIED EXPOSURE OR FLAMMABLE LIMITS.

OTHER:

CONSUMPTION OF FOOD AND BEVERAGE SHOULD BE AVOIDED IN WORK AREAS WHERE HYDROCARBONS ARE PRESENT. ALWAYS WASH HANDS AND FACE WITH SOAP AND WATER BEFORE EATING, DRINKING, OR SMOKING.

VI. FIRE PROTECTION INFORMATION

FLASH POINT: APP. 420 F TEST METHOD: D-92
AUTOIGNITION TEMPERATURE: NO DATA TEST METHOD: NO DATA
FLAMMABLE LIMITS IN AIR % BY VOLUME
LOWER: NO DATA
UPPER: NO DATA

EXTINGUISHING MEDIA:

USE DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

SPECIAL FIRE FIGHTING PROCEDURES:

WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

UNUSUAL FIRE AND EXPLOSIVE CONDITIONS:

DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION.

VII. REACTIVITY DATA

STABILITY (THERMAL, LIGHT, ETC.): STABLE
CONDITIONS TO AVOID: NONE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: NONE
INCOMPATIBILITY MATERIALS TO AVOID:
MAY REACT WITH STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCTS:
NONE

VIII. ENVIRONMENTAL PRECAUTIONS

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONSULT HEALTH EFFECT INFORMATION IN SECTION III, PERSONAL HEALTH PROTECTION INFORMATION IN SECTION V, FIRE PROTECTION INFORMATION IN SECTION VI, AND REACTIVITY DATA IN SECTION VII. NOTIFY APPROPRIATE AUTHORITIES OF SPILL. CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATERCOURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS, OR OTHER MEANS AND PLACED IN DRUMS OR OTHER SUITABLE CONTAINERS.

WASTE DISPOSAL METHOD:

ALL DISPOSALS MUST COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS. THE MATERIAL, IF SPILLED OR DISCARDED, MAY BE A REGULATED WASTE. REFER TO STATE AND LOCAL REGULATIONS. CAUTION! IF REGULATED SOLVENTS ARE USED TO CLEAN UP SPILLED MATERIAL, THE RESULTING WASTE MIXTURE MAY BE REGULATED. DEPARTMENT OF TRANSPORTATION (DOT) REGULATIONS MAY APPLY FOR TRANSPORTING THIS MATERIAL WHEN SPILLED. WASTE MATERIAL MAY BE LANDFILLED OR

INCINERATED AT AN APPROVED FACILITY. MATERIALS SHOULD BE RECYCLED IF POSSIBLE.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA): No chemicals in this material with known CAS numbers are subject to the reporting requirements of CERCLA

IX. MISCELLANEOUS

HANDLING AND STORAGE REQUIREMENTS:

DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS. THIS PRODUCT IS NOT CLASSIFIED AS HAZARDOUS UNDER DOT REGULATIONS. FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106—FLAMMABLE AND COMBUSTIBLE LIQUIDS.

ADDITIONAL INFORMATION:

THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY SARA TITLE III, SECTION 313 REPORTABLE CHEMICALS AT OR GREATER THAN 1.0% (0.1% FOR CARCINOGENS). THIS PRODUCT IS ON THE TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY.

X. PHYSICAL PROPERTIES

BOILING POINT: APPROXIMATELY 655 F

MELTING POINT: N/A

APPEARANCE: TRANSPARENT WATER-WHITE LIQUID

ODOR: ODORLESS

VAPOR PRESSURE: < 1MM HG @ 70 F

SOLUBILITY: SOLUBLE IN HYDROCARBONS

PERCENT VOLATILE: NIL

VAPOR DENSITY (AIR=1): > 1

EVAPORATION RATE (EE=1): < 1

SPECIFIC GRAVITY: APP. 0.882 @ 60/60 F

MOLECULAR WEIGHT: VARIES

The information contained herein is based on data considered to be accurate. However, no warranty is expressed regarding the accuracy of these data or the results to be obtained from the use thereof. It is the user's obligation to determine the conditions of safe use of the product.